

# PRODUCT DATA SHEET

# **OXYGEN-FREE COPPER ANODES**

QUALITY SYSTEM CERTIFIED TO ISO 9001:2015

# **PRODUCT SPECIFICATION**

IMC 314 - OXYGEN-FREE COPPER

Copper <sup>(1)</sup>	99.95 MIN%
Iron	0.003 MAX%
Sulfur	0.003 MAX%
Lead	0.002 MAX%
Antimony	0.002 MAX%
Nickel	0.002 MAX%
Arsenic	0.001 MAX%
Tin	0.002 MAX%
Total Other <sup>(2)</sup>	0.010 MAX%
Oxygen	0.0035 MAX%

- (1) Copper includes Silver
- (2) Other metallic elements include: Bi, Cd, Mn, Hg, Se, Te, Zn



#### SIZES

OXYGEN-FREE COPPER NUGGETS & BALLS

.56" x .5" / 14mm x 12.5mm .56" x .75" / 14mm x 19mm .75" x .75" / 19mm x 19mm 1" x 1" / 25mm x 25mm 1.375" x 1.5" / 35mm x 38mm

25mm / 1.0" (Balls) 50mm / 2.0" (Balls)

19mm / .75" (Balls)



# PACKAGING

- 44 lb Boxes / 20 Kg
   2200 lb Pallets / 1000 Kg
- 220 lb Drums / 100 Kg
   1980 lb Pallets / 900 Kg
- Bulk Packaging Available

#### **FEATURES**

- Hot rolling produces a fine-grained structure.
- Consistent dissolution.
- Consistent surface area.
- Quick-settling characteristics avoid bridging, voids and basket damage. (Balls)
- Perfect for automated chute loading. (Balls)
- For use in any anode basket or tray.
- · Special process eliminates precleaning.
- Color-coded, user-friendly packaging.
- Certificate of Analysis issued for every lot.

### **TYPICAL APPLICATIONS**

- Ammunition
- Coinage
- Corrosion Protection in Automotive Parts
- Decorative Plating
- Electrical Connectors
- Electronic Components
- Power Distribution Equipment
- Wire Plating
- Alloying

This information herein is believed to be reliable, however, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose.

The manufacturer shall not be liable to damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patents.